



## INTRODUCTION

Aksa power generation system, providing optimum performance, and reliability, for stationary standby, prime power, and continuous duty applications. All generator sets are factory build, and production tested.

### Power (kVA)

3 Phase, 50 Hz, PF 0.8

| VOLTAGE | STANDBY RATING (ESP) |         | PRIME RATING (PRP) |         | Standby Amper |
|---------|----------------------|---------|--------------------|---------|---------------|
|         | kW                   | kVA     | kW                 | kVA     |               |
| 400/231 | 880,00               | 1100,00 | 800,00             | 1000,00 | 1587,76       |

**STANDBY RATING (ESP)** Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. ESP is in accordance with ISO 8528-1. Overload is not allowed.

**PRIME RATING (PRP)** Applicable for supplying power to varying electrical load for unlimited hours. PRP is in accordance with ISO 8528-1. 10 % overload capability is available for a period of 1 hour within 12-hour period of operation.

## General Characteristics

|                           |                       |
|---------------------------|-----------------------|
| Model Name                | APD 1100 BD           |
| Frequency (Hz)            | 50                    |
| Fuel Type                 | Diesel                |
| Engine Made and Model     | BAUDOUIN 12M26G1100/5 |
| Alternator Made and Model | AK 7825               |
| Control Panel Model       | DSE 7320              |
| Canopy                    | MS 88                 |

## ENGINE SPECIFICATIONS

|                                       |  |
|---------------------------------------|--|
| Engine                                | BAUDOUIN                                 |
| Engine Model                          | 12M26G1100/5                             |
| Number of Cylinder (L)                | 12 cylinders - V type                    |
| Bore (mm.)                            | 150                                      |
| Stroke (mm.)                          | 150                                      |
| Displacement (lt.)                    | 31,8                                     |
| Aspiration                            | Turbo Charged and Air to Air AfterCooled |
| Compression Ratio                     | 15.7:1                                   |
| RPM (d/dk)                            | 1500                                     |
| Oil Capacity (Total With Filter) (lt) | 114                                      |
| Standby Power (kW/HP)                 | 973/1305                                 |
| Prime Power                           | 889/1192                                 |
| Block Heater QTY                      | 2  |
| Block Heater Power (Watt)             | 3000                                     |
| Fuel Type                             | Diesel                                   |
| Injection Type and System             | Direct                                   |
| Type of Fuel Pump                     | Mechanical                               |
| Governor System                       | Electronic                               |
| Operating Voltage (Vdc)               | 24 Vdc                                   |



|   |              |
|---|--------------|
| Battery and Capacity (Qty/Ah)                       | 2x143        |
| Charge Alternator (A)                               | 55           |
| Cooling Method                                      | Water Cooled |
| Cooling Fan Air Flow (m3/min)                       | 840          |
| Coolant Capacity (engine only / with radiator) (lt) | 83/139       |
| Air Filter  | Dry Type     |
| Fuel Cons. Prime With %100 Load (lt/hr)             | 207.1        |
| Fuel Cons. Prime With %75 Load (lt/hr)              | 155.3        |
| Fuel Cons. Prime With %50 Load (lt/hr)              | 106,6        |

### ALTERNATOR CHARACTERISTICS

|                             |         |
|-----------------------------|---------|
| Manufacturer                | Aksa    |
| Alternator Made and Model   | AK 7825 |
| Frequency (Hz)              | 50      |
| Power (kVA)                 | 1032    |
| VOLTAGE (V)                 | 400     |
| Phase                       | 3       |
| A.V.R.                      | MX341   |
| Voltage Regulation          | (+/-)1% |
| Insulation System           | H       |
| Protection                  | IP22    |
| Rated Power Factor          | 0.8     |
| WEIGHT COMP. GENERATOR (Kg) | 2394    |
| COOLING AIR (m³/min)        | 130.8   |

### Open Gen.Set Dimensions (mm)

|                     |      |
|---------------------|------|
| LENGTH              | 4200 |
| WIDTH               | 2204 |
| HEIGHT              | 2257 |
| TANK CAPACITY (lt.) | 1600 |

### Gen.Set Canopy Dimensions (mm)

|                     |      |
|---------------------|------|
| LENGTH              | 5513 |
| WIDTH               | 2260 |
| HEIGHT              | 2502 |
| TANK CAPACITY (lt.) | 1600 |

1. Steel structures.
2. Emergency stop push button.
3. Control panel is mounted on the baseframe . Located at the right side of the generator set.
4. Corrosion-resistant locks and hinges.
5. Oil could be drained via valve and a hose
6. Exhaust system in the canopy.



7. Special large access doors for easy maintenance
8. Base frame -fuel tank.
9. Lifting points similar to ISO container , located on each top corner of the canopy.
10. The cap on the canopy provides easy access to radiator cap.
11. Sound proofing materials
12. Plastic air intake pockets.

## INTRODUCTION

Sound-attenuated and weather protective enclosures for generating sets from Aksa, meet even the sound requirements and provide optimum protection from inclement weather and development by our specialist acoustic engineers. Our modular designed sound insulated canopies provide ease of access for servicing and general maintenance and interchangeable components permitting on-site repair. Enclosures are designed to optimize genset cooling performance, providing you with confidence that genset ratings and ambient capability.

## Control Panel

|                      |   |
|----------------------|---|
| Control Module       | DSE   |
| Control Module Model | DSE 7320  |
| Communication Ports  | MODBUS  |
|                      | <ol style="list-style-type: none"><li>1. Menu navigation buttons</li><li>2. Close mains button</li><li>3. Main Status and instrumentation display</li><li>4. Alarm LED's</li><li>5. Close generator button</li><li>6. Status LED's</li><li>7. Operation selecting buttons</li></ol> |

## Devices

DSE 7320 Auto Mains Failure control module

Static battery charger

Emergency stop push button and fuses for control circuits

## CONSTRUCTION and FINISH

Components installed in a sheet steel enclosure.

Phosphate chemical, pre-coating of steel provides corrosion resistant surface

Polyester composite powder topcoat forms a high gloss and extremely durable finish

Lockable hinged panel door provides for easy component access

## INSTALLATION

Control panel is mounted to gen-set baseframe on robust steel stand or power module. Located on the side of generating set with proper panel visibility.

## GENERATING SET CONTROL UNIT

The DSE 7320 control module is a standard addition to our generator sets from 220 kVA upwards and it has been designed to start and stop diesel and gas generating sets that include electronic and non-electronic engines.

The DSE 7320 includes the additional capability of being able to monitor a mains (utility) supply and is, therefore, suitable for controlling a standby generating set in conjunction with an automatic transfer switch.

The DSE7320 also indicates operational status and fault conditions, automatically shutting down the generating set and indicating faults by means of its LCD display on the front panel.

## STANDARD SPECIFICATIONS

Microprocessor controlled

- 132 x 64 pixel LCD display makes information easy to read



- Front panel programming and also via PC software
- Soft touch membrane keypad and five key menu navigation
- Remote communications via RS232, RS485 and ethernet.
- Event logging (50) showing date and time
- Multiple date and time engine exercise mode and maintenance scheduler
- Engine block heater control.
- Controls; stop, manual, auto, test, start, mute lamb test/transfer to generator, transfer to mains, menu navigation.

### Instruments

#### ENGINE

Engine speed  
Oil pressure  
Coolant temperature  
Run time Battery volts  
Engine maintenance due

#### GENERATOR

Voltage (L-L, L-N)  
Current (L1-L2-L3)  
Frequency  
Earth current

kW

Pf

kVAr

kWh, kVAh, kVArh

Phase sequence

#### MAINS

Voltage (L-L, L-N)  
Frequency

#### WARNING

Charge failure  
Battery under voltage  
Fail to stop  
Low fuel level (opt.)  
kW overload  
Negative phase sequence

Loss of speed signal

#### PRE-ALARMS

Low oil pressure  
High engine temperature



Low engine temperature  
Over /Under speed  
Under/over generator frequency  
Under/over generator voltage  
ECU warning  
SHUTDOWNS  
Fail to start  
Emergency stop  
Low oil pressure  
High engine temperature  
Low coolant level  
Over /Under speed  
Under/over generator frequency  
Under/over generator voltage  
Oil pressure sensor open  
Phase rotation  
ELECTRICAL TRIP  
Earth fault  
kW overload  
Generator over current  
Negative phase sequence

#### **Options**

High oil temperature shut down  
Low fuel level shut down  
Low fuel level alarm  
High fuel level alarm  
EXPANSION MODULES  
Additional LED module (2548)  
Expansion relay module (2157)  
Expansion input module (2130)

#### **Standards**

Electrical Safety / EMC compatibility  
BS EN 60950 Electrical business equipment  
BS EN 61000-6-2 EMC immunity standard  
BS EN 61000-6-4 EMC emission standard

#### **STATIC BATTERY CHARGER**

Battery charger is manufactured with switching-mode and SMD technology and it has high efficiency.  
Battery charger models' output V-I characteristic is very close to square



2405 has fully output short circuit protection and it can be used as a current source.

2405 charger has high efficiency, long life, low failure rate, lightweight and low heat radiated in accordance with linear alternatives.

The charger is fitted with a protection diode across the output.

Charge fail output is available.

Connect charge fail relay coil between the positive output and CF output.

Input: 196-264V.

Output: 27,6V 5A or 13,8V 5A.

## STANDARD SPECIFICATIONS

- Water cooled, Diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Engine coolant heater
- Base frame design incorporates an integral fuel tank and anti-vibration isolators
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel bellows supplied separately(for open sets)
- Static battery charger
- Manual for application and installation
- Generators Sets' voltage and frequency regulation comply with ISO 8528-5

## OPTIONAL EQUIPMENTS

### ENGINE

Fuel-Water Separator Filter

Oil heater

### ALTERNATOR

Anti-Condensation Heater

Over sized alternator

PMG excitation + AVR

Main line circuit breaker

### CONTROL SYSTEM

Automatic synchronising and power control system ( multi gen-set Parallel )

Transition synchronization with mains

Remote annunciator panel

Remote relay output

Alarm output relays

Remote communication with modem

Earth fault, single set



Charge Ammeter

**TRANSFER SWITCH**

Three Pole Contactor

Four Pole Contactor

Three or four pole motor operated circuit breaker

**OTHER ACCESSORIES**

Main Fuel Tank

Automatic or manual fuel filling system

Manual oil drain pump

Electrical oil drain pump

Low and high fuel level alarm

Residential silencer

Enclosure: weater protective or sound attenuated

Duct adapter ( on radiator)

Inlet and outlet motorised louvers

Inlet and outlet acoustic baffles

Trailer

Tool kit for maintenance

Automatic transfer switch

**AKSA CERTIFICATES**

- TS ISO 8528

- CE

- SZUTEST

- 2000/14/EC